

INTERCHANGE CHART

TYPE	FLOW CAPACITY	TYPE	*TWIN FILTERS AVAILABLE
D E L A V A N	.40-2.25 2.50-10.00 .40-4.00 4.50-28.00 .50-3.00	H* PH S* SS Q* MH	Hollow Cone More Hollow Solid Cone Semi-Solid Cone Special Mobile Home
D A N F O S S	.40-4.00 .40-2.25 2.50-10.00 4.50-28.00	S* H* PH SS	Solid Cone Hollow Cone More Hollow Semi-Solid Cone

S T E I N E N

S T E I N E N

TYPE	FLOW CAPACITY	TYPE	*TWIN FILTERS AVAILABLE
H H B SS SS P	.40-2.25 2.50-10.00 .40-4.00 .50-3.00 4.50-28.00 ALL	H* PH S* Q* SS S*	Hollow Cone More Hollow Solid Cone Special Semi-Solid Cone Solid Cone
F L U I D I C S	.40-.55 .60-4.00 .40-.55 .60-2.25	S* S H* H	Solid Cone Solid Cone Hollow Cone Hollow Cone

S T E I N E N

S T E I N E N

Oil Burner Nozzles

Since 1907

Quality, Technology, Efficiency -
Because it Does Matter

WM. STEINEN MFG. CO.

29 East Halsey Road, Parsippany, NJ 07054

Phone: 973-887-6400 • FAX: 973-887-4632

www.steinen.com

Twin-Filter Nozzle*



STEINEN

NOZZLES

STEINEN

NOZZLES

Approximate Capacities at Various Pressures

Rated Flow at 100 P.S.I.	U.S. Gallons per Hour					
	Pressure P.S.I.					
G.P.H.	125	145	175	200	250	300
0.40	0.45	0.48	0.53	0.57	0.63	0.69
0.45	0.50	0.54	0.60	0.64	0.71	0.78
0.50	0.56	0.60	0.66	0.71	0.79	0.87
0.55	0.62	0.66	0.73	0.78	0.87	0.95
0.60	0.67	0.72	0.79	0.85	0.95	1.04
0.65	0.73	0.78	0.86	0.92	1.03	1.13
0.75	0.84	0.90	0.99	1.06	1.19	1.30
0.85	0.95	1.02	1.12	1.20	1.34	1.47
0.90	1.01	1.08	1.19	1.27	1.42	1.56
1.00	1.12	1.20	1.32	1.41	1.58	1.73
1.10	1.23	1.32	1.46	1.56	1.74	1.91
1.20	1.34	1.45	1.59	1.70	1.90	2.08
1.25	1.40	1.51	1.65	1.77	1.98	2.17
1.35	1.51	1.63	1.79	1.91	2.13	2.34
1.50	1.68	1.81	1.98	2.12	2.37	2.60
1.65	1.84	1.99	2.18	2.33	2.61	2.86
1.75	1.96	2.11	2.32	2.47	2.77	3.03
2.00	2.24	2.41	2.65	2.83	3.16	3.46
2.25	2.52	2.71	2.98	3.18	3.56	3.90
2.50	2.80	3.01	3.31	3.54	3.95	4.33
2.75	3.07	3.31	3.64	3.89	4.35	4.76
3.00	3.35	3.61	3.97	4.24	4.74	5.20
3.50	3.91	4.21	4.63	4.95	5.53	6.06
4.00	4.47	4.82	5.29	5.66	6.32	6.93
4.50	5.03	5.42	5.95	6.36	7.12	7.79
5.00	5.59	6.02	6.61	7.07	7.91	8.66
5.50	6.15	6.62	7.28	7.78	8.70	9.53
6.00	6.71	7.23	7.94	8.49	9.49	10.4
6.50	7.27	7.83	8.60	9.19	10.3	11.3
7.00	7.83	8.43	9.26	9.90	11.1	12.1
7.50	8.39	9.03	9.92	10.6	11.9	13.0
8.00	8.94	9.63	10.6	11.3	12.7	13.9
9.00	10.1	10.8	11.9	12.7	14.2	15.6
10.00	11.2	12.0	13.2	14.1	15.8	17.3
11.00	12.3	13.2	14.6	15.6	17.4	19.1
12.00	13.4	14.5	15.9	17.0	19.0	20.8
13.00	14.5	15.7	17.2	18.4	20.6	22.5
14.00	15.7	16.9	18.5	19.8	22.1	24.2
15.00	16.8	18.1	19.8	21.2	23.7	26.0
16.00	17.9	19.3	21.2	22.6	25.3	27.7
17.00	19.0	20.5	22.5	24.0	26.9	29.4
18.00	20.1	21.7	23.8	25.5	28.5	31.2
20.00	22.4	24.1	26.5	28.3	31.6	34.6
22.00	24.6	26.5	29.1	31.1	34.8	38.1
24.00	26.8	28.9	31.8	33.9	37.9	41.6
26.00	29.1	31.3	34.4	36.8	41.1	45.0
28.00	31.3	33.7	37.0	39.6	44.3	48.5

Oil Standards: 3.4 cst. viscosity, .84 density @ 20 C per EN 293

Twin-Filter Nozzle



WM. STEINEN MFG. CO.

29 East Halsey Road, Parsippany, NJ 07054

Phone: 973-887-6400 • FAX: 973-887-4632

www.steinen.com



Oil Burner Nozzles

Since 1907

Quality, Technology, Efficiency -

Because it Does Matter